

Wymiary standardowych uszczeltek do kołnierzy zgodnie z PN EN 1514-1/1997

DN	d1 [mm]	PN 2,5	PN 6	PN 10	PN 16	PN 25	PN 40	d1 [mm]	PN 63
		d2 [mm]	d2 [mm]	d2 [mm]	d2 [mm]	d2 [mm]	d2 [mm]		d2 [mm]
10	18	39	39	46	46	46	46	18	56
15	22	44	44	51	51	51	51	21	61
20	27	54	54	61	61	61	61	25	72
25	34	64	64	71	71	71	71	30	82
32	43	76	76	82	82	82	82	41	88
40	49	86	86	92	92	92	92	47	103
50	61	96	96	107	107	107	107	59	113
60	72	106	106	117	117	117	117	68	123
65	77	116	116	127	127	127	127	73	138
80	89	132	132	142	142	142	142	86	148
100	115	152	152	162	162	168	168	110	174
125	141	182	182	192	192	194	194	135	210
150	169	207	207	218	218	224	224	163	247
175	-	-	-	-	-	-	-	185	277
200	220	262	262	273	273	284	290	210	309
250	273	317	317	328	329	340	352	260	364
300	324	373	373	378	384	400	417	314	424
350	356	423	423	438	444	457	474	360	486
400	407	473	473	489	495	514	546	415	-
450	458	528	528	539	555	564	571	-	-
500	508	578	578	594	617	624	628	-	-
600	610	679	679	695	734	731	747	-	-
700	712	784	784	810	804	833	-	-	-
800	813	890	890	917	911	942	-	-	-
900	915	990	990	1017	1011	1042	-	-	-
1000	1016	1090	1090	1124	1128	1154	-	-	-
1100	1120	-	-	1231	1228	1254	-	-	-
1200	1220	1290	1290	1341	1342	1364	-	-	-

d1 – średnica wewnętrzna,

d2 – średnica zewnętrzna,

DN – średnica nominalna,

PN – ciśnienie nominalne

Wymiary DN – cal

DN	10	15	20	25	32	40	50	65	80	100	125	150
cal	$\frac{3}{8}$	$\frac{1}{2}$	$\frac{3}{4}$	1"	$1\frac{1}{4}$	$1\frac{1}{2}$	2"	$2\frac{1}{2}$	3"	4"	5"	6"
DN	200	250	300	350	400	450	500	600	700	800	900	1000
cal	8"	10"	12"	14"	16"	18"	20"	24"	28"	32"	36"	40"